## PATENT ABSTRACTS OF JAPAN

(11)Publication number:

07-060955

(43) Date of publication of application: 07.03.1995

(51)Int.Cl.

B41J 2/01

B41J 2/175

(21) Application number: **05-214031** 

(71)Applicant: CANON INC

(22) Date of filing:

30.08.1993

(72)Inventor: ASAI AKIRA

## (54) INK JET RECORDING HEAD AND INK JET RECORDER EQUIPPED WITH THE RECORDING HEAD

$$\mathbf{i}(\mathbf{r}) = \frac{\bar{\mathbf{I}}}{\theta \, \mathrm{rd}(\mathbf{r})}$$

(57) Abstract:

π

Di.

PURPOSE: To obtain a recording head having a novel heating element wherein heating distribution on a surface of a resistor is equalized and its recorder by a method wherein a heating resistor has a heating part of an approximately circularly annular or fan-like annular surface shape, and its thickness is varied inversely proportional to a distance in a radial direction from a central point of the surface shape.

 $q(r) = i(r)^2 \rho d(r)$ 

CONSTITUTION: When voltage is impressed by making a current (I) flow radially along a radial direction of a heating resistor, a thickness d (r) of a heating part of the heating resistor is varied inversely proportional to a radial distance (r) from a center of a surface shape. Thereby, a current density i (r) at any point on the heating part at a radial distance (r) apart from the center

 $\langle q(r) \rangle = \frac{I^2 \rho}{\theta^2 r^2 d(r)}$ 

formula  $\theta$  is an angle of a fan-like annulus ( $2\pi$  in the case of a circular annulus). Relation between 'the resistivity ( $\rho$ ) of the resistor and a heating value q (r) per unit time unit area is as given by the formula II. Therefore, the

comes to be as given by the formula (I). In the

LEGAL STATUS

formula III is obtained.

[Date of request for examination]

30.06.1999

[Patent number]

3157964

[Date of registration]

09.02.2001